jGun™ Kit for 501F/G 701F/G

Combustion Can Cover Removal Tool



- Assembly weight nominally 15.5 lbs
- Fitted Reaction Arm Interface
- 1,000 FT LB Pneumatic jGun Single Speed.
- Same Kit for Breakout and Rundown
- Accuracy to 5%, sustained for entire job
- Full breakout achievable in 2-3 hours, high gain in productivity
- Suitable for other bolting needs
- Durability
- Unmatched Speed and Safety
- Pneumatic pressure range from 20-90 PSI







The Future of Bolting



- Made In USA
- **Quiet Operation**
- ZERO Vibration or Impact
- **Continuous Torque Rotation**
- Easy to Operate Ergonomic Design
- Applies Torque or Tension to Fasteners
- Accurate, Adjustable & Repeatable Torque
- Covered by Full Complimentary 1 Year Warranty



SOCKETS

Male and Female, Hex and Allen Sockets.



EXTENSIONS

Job Specific and Custom Drive Extensions.



JACKSCREW NUT ADAPTER

Customized Solutions for Every Type of Application.



FRL UNIT W/SILENCER

Filter, Regulator and Lubrication Unit. For use with all torque guns. Optional Silencer Unit to reduce operational noise by 35%, down to a very low 70-75 Db.



This safety mechanism drastically reduces operator error. The lever must be depressed while pulling the trigger, ensuring operator keeps hands away from pinch points.



OFFSET LINK

Offset links For Limited Clearance. Perfect for plate heat exchangers.



AIR DRYER

Removes moisture from lines. For use on all air powered equipment.

